

**PRODUCT
DATA SHEET**

Essentials 150

Vinyl Collection 2014

January 2014

Type of flooring

ISO 26986

Vinyl Floorcovering

Class of use

ISO 10874





Class


21


Description





 **ISO 24346** **1,50 mm**
(EN 428)


 **ISO 24340** **0,15 mm**
(EN 429)


 **ISO 24341** **35 m**
4+3+2m
(EN 426)

 **ISO 23997** **1,210 kg/m²**
(EN 430)


 **EN 660-2** **T**
Abrasion group


 **ISO 4918** **NO**
(EN 425)
Castor wheel test


 **EN ISO 717/2** **ca. 12 dB**
Impact sound absorption


 **ISO 24343-1** **≤ 0,35 mm**
(EN 433)
Static indentation

Other Characteristics


 **ISO 105/B02** **≥ 6**
Light fastness


 **ISO 23999** **≤ 0,40 %**
(EN 434)
Dimensional stability


 **ISO 10456** **0,02 m²/kW**
(EN 12524)
Thermal resistance
for underfloor heating

 **Slip resistance**
EN 13893 **μ ≥ 0,30**
DIN 51130 **R10**

 **Recyclable** **OK**

 **Chemical resistance** **OK**

 **Fire Classification**
EN 13501-1 **Bfl-s1**
Report N° : **RA10-0251**

 **EN 1815** **≤ 2 kV**
Static electrical
propensity



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.